

# TEMPOFLUX 2 direct flush valve

Ref. 762150

Direct flush WC valve






## DESCRIPTION

TEMPOFLUX 2 direct flush valve - Ref. 762150

Flush system without cistern: directly connected to pipework.  
 For walls  $\leq 140\text{mm}$ .  
 3L/6L dual flush can be adjusted to 2L/4L.  
 Soft-touch operation.  
 Vacuum breaker.  
 Integrated stopcock and flow rate / flush volume adjuster.  
 Solid brass body.  
 Chrome-plated metal push-button.  
 In-line inlet  $M\frac{3}{4}"$ .  
 Outlet connection for PVC tube  $\varnothing 26/32\text{mm}$ .  
 Threaded rod can be cut to size.  
 Acoustic level complies with European standard EN 12541 class II.  
 Base flow rate: 1 L/sec at 1 bar dynamic pressure.  
 Compatible with rain water.  
 Suitable for rimless WC pans without flow rate regulation.  
 Suitable for people with reduced mobility.  
 10-year warranty.

## TECHNICAL CHARACTERISTICS

TEMPOFLUX 2 direct flush valve - Ref. 762150

Connector	$\frac{3}{4}"$
Technology	Time flow
Length	140mm
Flow rate	3L/6L
Norms	 
Warranty	

## ADVANTAGES



Soft-touch operation



Dual flush 3L/6L



No cistern: no stagnant water



Cross wall installation

