

# SECURITHERM BIOCLIP

## thermostatic sink mixer

Ref. H9614P

Wall-mounted sequential thermostatic mixer






### DESCRIPTION

**SECURITHERM BIOCLIP thermostatic sink mixer - Ref. H9614P**





Wall-mounted SECURITHERM thermostatic sink mixer.  
 Thermostatic sequential mixer: opens and closes with cold water.  
 No risk of cross flow between hot and cold water.  
 No non-return valves on the inlets.  
 Wall-mounted mixer supplied with 2 stainless steel spouts L. 136mm.  
 Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.  
 Securitouch thermal insulation prevents burns.  
 Scale-resistant sequential thermostatic cartridge for sequential control of flow rate and temperature.  
 Temperature can be adjusted from cold water up to 40°C with temperature limiter set at 40°C.  
 Thermal or chemical shocks are possible.  
 Body and spout with smooth interiors and low water volume.  
 Flow rate regulated at 7 lpm.  
 Chrome-plated brass body.  
 No manual contact thanks to Hygiene control lever L. 146mm.  
 Mixer with 200mm centres, supplied with 2 in-line STOP/CHECK M1/2" M3/4" connectors ideal for hospitals.  
 Thermostatic mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
 Suitable for people with reduced mobility.  
 Mixer with 10-year warranty.

### TECHNICAL CHARACTERISTICS

**SECURITHERM BIOCLIP thermostatic sink mixer - Ref. H9614P**

Connector	M1/2"
Technology	SECURITHERM BIOCLIP sequential mixer
Height	141mm
Width	234mm
Spout length	136mm
Flow rate	7 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	 
Warranty	

### ADVANTAGES

-  Sequential: opens/closes with cold water
-  Maximum hygiene: no non-return valves
-  Removable spout: reduces bacterial development
-  SECURITHERM: optimum anti-scalding safety

