

SECURITHERM thermostatic basin mixer

Ref. H960015

Single hole thermostatic sequential mixer, H. 95mm L. 120mm

DESCRIPTION

SECURITHERM thermostatic basin mixer - Ref. H960015

Deck-mounted SECURITHERM thermostatic basin mixer. Thermostatic sequential mixer: opens and closes with cold water.

No risk of cross flow between hot and cold water. No non-return valves on the inlets.

Anti-scalding failsafe: shut-offs automatically if cold or hot water supply fails.

Securitouch thermal insulation prevents burns.

Single hole mixer with curved spout H. 95mm L. 120mm, equipped with a hygienic flow straightener with no impurity retention and will withstand thermal shocks.

Scale-resistant sequential thermostatic cartridge for single lever control of the flow rate and temperature.

Temperature control from cold water up to 40°C with temperature limiter set at 40°C.

Thermal or chemical shocks are possible.

Body and spout with smooth interiors and low water volume. Flow rate limited to 5 lpm at 3 bar.

No manual contact thanks to Hygiene control lever L. 146mm. No pop-up waste.

PEX flexibles F3/8" supplied with stopcocks in chrome-plated brass, filters and Ø 15mm compression fittings.

Fixing reinforced by 2 stainless steel rods.

Mixer ideal for healthcare facilities, nursing homes, hospitals and clinics.

Mixer Suitable for people with reduced mobility.

Mixer with 30-year warranty.

Also available with copper tails.

TECHNICAL CHARACTERISTICS

SECURITHERM thermostatic basin mixer - Ref. H960015

Connector	M1/2" Ø 15mm
Technology	SECURITHERM Securitouch sequential mixer
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass



ADVANTAGES



Sequential: opens/closes with cold water




Maximum hygiene: no non-return valves



SECURITHERM: optimal anti-scalding safety



Securitouch: thermal insulation prevents burns



Norms



Warranty



Repairability

